

Tomago Aluminium Remelt Ingot

Tomago Aluminium Co. P/L

Chemwatch Hazard Alert Code: 1

Chemwatch: 7502-31

Issue Date: 19/07/2018

Version No: 6.1.1.1

Print Date: 08/08/2018

Safety Data Sheet according to WHS and ADG requirements

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Tomago Aluminium Remelt Ingot
Synonyms	Ingot Aluminium Remelt, Aluminium Standard Ingot, Primary Aluminium Ingot
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Feedstock for manufacturing aluminium parts and products.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Tomago Aluminium Co. P/L
Address	33 Tomago Road Tomago NSW 2322 Australia
Telephone	(02) 49 669 669
Fax	(02) 49 669 711
Website	Not Available
Email	Not Available

Emergency telephone number



Association / Organisation	Not Available
Emergency telephone numbers	(02) 49 669 669
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	1		0 = Minimum 1 = Low
Body Contact	1		2 = Moderate
Reactivity	0		3 = High
Chronic	0		4 = Extreme

Poisons Schedule	Not Applicable
Classification	Not Applicable

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
		welding ingots containing
7429-90-5	>60	<u>aluminium</u>
7440-21-3	<10	<u>silicon</u>
7439-89-6	<1	<u>iron</u>
7440-66-6	<0.1	<u>zinc</u>
7440-50-8	<0.1	<u>copper</u>
7440-47-3	<0.1	<u>chromium</u>
7440-42-8	<0.1	<u>boron</u>
7440-32-6	<0.1	<u>titanium</u>
7440-24-6	<0.1	<u>strontium</u>
7440-02-0	<0.1	<u>nickel</u>
7439-96-5	<0.1	<u>manganese</u>
7439-95-4	<0.1	<u>magnesium</u>
		which upon use generates
Not Available	NotSpec.	<u>welding fumes</u>
1344-28-1.	NotSpec.	<u>fresh alumina</u>
99439-28-8	NotSpec.	<u>silica, fumed</u>
1309-37-1.	NotSpec.	<u>iron oxide fume</u>
1309-48-4	NotSpec.	<u>magnesium oxide fume</u>
7440-50-8.	NotSpec.	<u>copper fume</u>
7439-96-5.	NotSpec.	<u>manganese fume</u>
7440-47-3	NotSpec.	<u>chromium fume</u>
7440-02-0	NotSpec.	<u>nickel fume</u>
1314-13-2	NotSpec.	<u>zinc oxide fume</u>
		action of arc on air may generate
Mixture	NotSpec.	<u>nitrogen oxides</u>
10028-15-6	NotSpec.	<u>ozone</u>

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

Eye Contact	<ul style="list-style-type: none"> Particulate bodies from welding spatter may be removed carefully. DO NOT attempt to remove particles attached to or embedded in eye. Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye. Seek urgent medical assistance, or transport to hospital. Arc rays can injure eyes
Skin Contact	If skin or hair contact occurs: <ul style="list-style-type: none"> Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. Arc rays can burn skin
Inhalation	<ul style="list-style-type: none"> If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	Not normally a hazard due to physical form of product.

Indication of any immediate medical attention and special treatment needed

Copper, magnesium, aluminium, antimony, iron, manganese, nickel, zinc (and their compounds) in welding, brazing, galvanising or smelting operations all give rise to thermally produced particulates of smaller dimension than may be produced if the metals are divided mechanically. Where insufficient ventilation or respiratory protection is available these particulates may produce "metal fume fever" in workers from an acute or long term exposure.

- Onset occurs in 4-6 hours generally on the evening following exposure. Tolerance develops in workers but may be lost over the weekend. (Monday Morning Fever)
- Pulmonary function tests may indicate reduced lung volumes, small airway obstruction and decreased carbon monoxide diffusing capacity but these abnormalities resolve after several months.
- Although mildly elevated urinary levels of heavy metal may occur they do not correlate with clinical effects.
- The general approach to treatment is recognition of the disease, supportive care and prevention of exposure.

Continued...

- Seriously symptomatic patients should receive chest x-rays, have arterial blood gases determined and be observed for the development of tracheobronchitis and pulmonary edema.

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Welding electrodes should not be allowed to come into contact with strong acids or other substances which are corrosive to metals. Welding arc and metal sparks can ignite combustibles.
-----------------------------	---

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear breathing apparatus plus protective gloves in the event of a fire. ▸ Prevent, by any means available, spillage from entering drains or water courses. ▸ Use fire fighting procedures suitable for surrounding area.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▸ Non combustible. ▸ Not considered to be a significant fire risk, however containers may burn. ▸ In a fire may decompose on heating and produce toxic / corrosive fumes.
HAZCHEM	Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<p>Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use dry clean up procedures and avoid generating dust. Place in suitable containers for disposal.</p>
Major Spills	<p>Minor hazard.</p> <ul style="list-style-type: none"> ▸ Clear area of personnel. ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Control personal contact with the substance, by using protective equipment if risk of overexposure exists.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▸ Limit all unnecessary personal contact. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Avoid contact with incompatible materials.
Other information	<ul style="list-style-type: none"> ▸ Keep dry. ▸ Store under cover. ▸ Protect containers against physical damage. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▸ Packaging as recommended by manufacturer. ▸ Check that containers are clearly labelled
Storage incompatibility	Welding electrodes should not be allowed to come into contact with strong acids or other substances which are corrosive to metals.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	aluminium	Aluminium (welding fumes) (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium, pyro powders (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (metal dust)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	silicon	Silicon	10 mg/m3	Not Available	Not Available	Not Available

Tomago Aluminium Remelt Ingot

Australia Exposure Standards	copper	Copper (fume)	0.2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper, dusts & mists (as Cu)	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	chromium	Chromium (metal)	0.5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nickel	Nickel, metal	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nickel	Nickel, powder	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	manganese	Manganese, fume (as Mn)	1 mg/m3	3 mg/m3	Not Available	Not Available
Australia Exposure Standards	welding fumes	Welding fumes (not otherwise classified)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium oxide	Aluminium oxide	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	iron oxide fume	Iron oxide fume (Fe2O3) (as Fe)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	magnesium oxide fume	Magnesium oxide (fume)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper fume	Copper (fume)	0.2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper fume	Copper, dusts & mists (as Cu)	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	manganese fume	Manganese, fume (as Mn)	1 mg/m3	3 mg/m3	Not Available	Not Available
Australia Exposure Standards	chromium fume	Chromium (metal)	0.5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nickel fume	Nickel, powder	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nickel fume	Nickel, metal	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	zinc oxide fume	Zinc oxide (dust)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	zinc oxide fume	Zinc oxide (fume)	5 mg/m3	10 mg/m3	Not Available	Not Available
Australia Exposure Standards	ozone	Ozone	Not Available	Not Available	0.1 ppm / 0.2 mg/m3	Not Available

EMERGENCY LIMITS


Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
silicon	Silicon	45 mg/m3	100 mg/m3	630 mg/m3
iron	Iron	3.2 mg/m3	35 mg/m3	150 mg/m3
zinc	Zinc	6 mg/m3	21 mg/m3	120 mg/m3
copper	Copper	3 mg/m3	33 mg/m3	200 mg/m3
chromium	Chromium	1.5 mg/m3	17 mg/m3	99 mg/m3
boron	Boron	1.9 mg/m3	21 mg/m3	130 mg/m3
titanium	Titanium	30 mg/m3	330 mg/m3	2,000 mg/m3
strontium	Strontium	30 mg/m3	330 mg/m3	2,000 mg/m3
nickel	Nickel	4.5 mg/m3	50 mg/m3	99 mg/m3
manganese	Manganese	3 mg/m3	5 mg/m3	1,800 mg/m3
magnesium	Magnesium	18 mg/m3	200 mg/m3	1,200 mg/m3
fresh alumina	Aluminum oxide; (Alumina)	5.7 mg/m3	15 mg/m3	25 mg/m3
iron oxide fume	Iron oxide; (Ferric oxide)	15 mg/m3	360 mg/m3	2,200 mg/m3
magnesium oxide fume	Magnesium oxide	30 mg/m3	120 mg/m3	730 mg/m3
copper fume	Copper	3 mg/m3	33 mg/m3	200 mg/m3
manganese fume	Manganese	3 mg/m3	5 mg/m3	1,800 mg/m3
chromium fume	Chromium	1.5 mg/m3	17 mg/m3	99 mg/m3
nickel fume	Nickel	4.5 mg/m3	50 mg/m3	99 mg/m3
zinc oxide fume	Zinc oxide	10 mg/m3	15 mg/m3	2,500 mg/m3
ozone	Ozone	0.24 ppm	1 ppm	10 ppm

Ingredient	Original IDLH	Revised IDLH
aluminium	Not Available	Not Available
silicon	Not Available	Not Available
iron	Not Available	Not Available
zinc	Not Available	Not Available
copper	100 mg/m3	Not Available
chromium	250 mg/m3	Not Available
boron	Not Available	Not Available
titanium	Not Available	Not Available
strontium	Not Available	Not Available
nickel	Not Available	Not Available
manganese	Not Available	Not Available
magnesium	Not Available	Not Available
welding fumes	Not Available	Not Available
fresh alumina	Not Available	Not Available
silica, fumed	Not Available	Not Available
iron oxide fume	2,500 mg/m3	Not Available

Tomago Aluminium Remelt Ingot

magnesium oxide fume	750 mg/m ³	Not Available
copper fume	100 mg/m ³	Not Available
manganese fume	Not Available	Not Available
chromium fume	250 mg/m ³	Not Available
nickel fume	Not Available	Not Available
zinc oxide fume	500 mg/m ³	Not Available
nitrogen oxides	Not Available	Not Available
ozone	5 ppm	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p> <p>If risk of inhalation or overexposure exists, wear SAA approved respirator or work in fume hood.</p>
Personal protection	
Eye and face protection	<p>Welding helmet with suitable filter. Welding hand shield with suitable filter.</p> <ul style="list-style-type: none"> Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. Goggles or other suitable eye protection shall be used during all gas welding or oxygen cutting operations. Spectacles without side shields, with suitable filter lenses are permitted for use during gas welding operations on light work, for torch brazing or for inspection. For most open welding/brazing operations, goggles, even with appropriate filters, will not afford sufficient facial protection for operators. Where possible use welding helmets or handshields corresponding to EN 175, ANSI Z49:12005, AS 1336 and AS 1338 which provide the maximum possible facial protection from flying particles and fragments.
Skin protection	See Hand protection below
Hands/feet protection	Welding Gloves Safety footwear
Body protection	See Other protection below
Other protection	<p>Overalls</p> <ul style="list-style-type: none"> Eyewash unit. <p>Aprons, sleeves, shoulder covers, leggings or spats of pliable flame resistant leather or other suitable materials may also be required in positions where these areas of the body will encounter hot metal.</p>

Respiratory protection

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	NO P1 Air-line*	- -	NO PAPR-P1 -
up to 50 x ES	Air-line**	NO P2	NO PAPR-P2
up to 100 x ES	-	NO P3 Air-line*	-
100+ x ES	-	Air-line**	NO PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Grey-silvery coloured metal ingots; insoluble in water.		
Physical state	Solid	Relative density (Water = 1)	2.5-2.9
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	482-660	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	2467	Molecular weight (g/mol)	Not Applicable

Continued...

Tomago Aluminium Remelt Ingot

Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	<p>Harmful levels of ozone may be found when working in confined spaces. Symptoms of exposure include irritation of the upper membranes of the respiratory tract and lungs as well as pulmonary (lung) changes including irritation, accumulation of fluid (congestion and oedema) and in some cases haemorrhage. Exposure may aggravate any pre-existing lung condition such as bronchitis, asthma or emphysema.</p> <p>Shielding gases may act as simple asphyxiants if significant levels are allowed to accumulate. Oxygen monitoring may be necessary.</p> <p>The inhalation of small particles of metal oxide results in sudden thirst, a sweet, metallic foul taste, throat irritation, cough, dry mucous membranes, tiredness and general unwellness. Headache, nausea and vomiting, fever or chills, restlessness, sweating, diarrhoea, excessive urination and prostration may also occur.</p>
Ingestion	<p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Large doses of cellulose may be administered orally as non-nutritive bulk, with doses of up to 30 g/day tolerated as bulk laxative while extremely large oral doses may produce disturbances to the gut.</p> <p>Acute toxic responses to aluminium are confined to the more soluble forms.</p> <p>Not normally a hazard due to physical form of product.</p> <p>Poisonings rarely occur after oral administration of manganese salts because they are poorly absorbed from the gut.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p>
Skin Contact	<p>Ultraviolet (UV) radiation is generated by the electric arc in the welding process. Skin exposure to UV can result in severe burns, often without prior burning.</p> <p>Exposure to infrared (IR) radiation, produced by the electric arc and other flame cutting equipment, may heat the skin surface and the tissues immediately below the surface. Except for this effect, which can progress to thermal burns in some situations, infrared radiation is not dangerous to welders.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>Skin contact does not normally present a hazard, though it is always possible that occasionally individuals may be found who react to substances usually regarded as inert.</p> <p>Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Fumes evolved during welding operations may be irritating to the upper-respiratory tract and may be harmful if inhaled.</p> <p>The inhalation of small particles of metal oxide results in sudden thirst, a sweet, metallic foul taste, throat irritation, cough, dry mucous membranes, tiredness and general unwellness. Headache, nausea and vomiting, fever or chills, restlessness, sweating, diarrhoea, excessive urination and prostration may also occur.</p> <p>In animals, instilling silicon dust in the windpipe caused only slight damage to the epithelium.</p> <p>Carbon monoxide poisoning results in breathing problems, diarrhoea and shock. It combines with haemoglobin, the carrier of oxygen in the blood, much more easily than oxygen; the complex formed can disturb muscle function, especially the heart.</p> <p>Manganese fume is toxic and produces nervous system effects characterised by tiredness. Acute poisoning is rare although acute inflammation of the lungs may occur. A chemical pneumonia may also result from frequent exposure. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever".</p>
Eye	<p>Ultraviolet (UV) radiation can damage the lens of the eye. Many arc welders experience the condition known as "arc-eye", which is a sensation of sand in the eyes. The condition is caused by excessive eye exposure to UV. Exposure to ultraviolet rays may also increase the skin effects of some industrial chemicals (coal tar and cresol compounds, for example).</p> <p>Fumes from welding/brazing operations may be irritating to the eyes.</p> <p>The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.</p> <p>Though considered non-harmful, slight irritation may result from contact because of the abrasive nature of the aluminium oxide particles. Thus it may cause itching and skin reaction and inflammation.</p> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the</p>

Tomago Aluminium Remelt Ingot

	use of the material and ensure that any external damage is suitably protected.	
Chronic	<p>Principal route of exposure is inhalation of welding fumes from electrodes and workpiece. Reaction products arising from electrode core and flux appear as welding fume depending on welding conditions, relative volatilities of metal oxides and any coatings on the workpiece. Studies of lung cancer among welders indicate that they may experience a 30-40% increased risk compared to the general population. Since smoking and exposure to other cancer-causing agents, such as asbestos fibre, may influence these results, it is not clear whether welding, in fact, represents a significant lung cancer risk. Welding fume with high levels of ferrous materials may lead to particle deposition in the lungs (siderosis) after long exposure. This clears up when exposure stops. Chronic exposure to iron dusts may lead to eye disorders.</p> <p>Ozone is suspected to produce lung cancer in laboratory animals; no reports of this effect have been documented in exposed human populations.</p> <p>Other welding process exposures can arise from radiant energy UV flash burns, thermal burns or electric shock</p> <p>The welding arc emits ultraviolet radiation at wavelengths that have the potential to produce skin tumours in animals and in over-exposed individuals, however, no confirmatory studies of this effect in welders have been reported.</p> <p>Metal oxides generated by industrial processes such as welding may cause a number of potential health problems. Particles smaller than 5 microns in diameter (which may be breathed in) may cause reduction in lung function. Particles of less than 1.5 microns can be trapped in the lungs, and, depending on the nature of the particle, may cause further serious health consequences.</p> <p>Manganese is an essential trace element. Chronic exposure to low levels of manganese can include a mask-like facial expression, spastic gait, tremors, slurred speech, disordered muscle tone, fatigue, anorexia, loss of strength and energy, apathy and poor concentration.</p> <p>Long-term exposure to low levels of carbon monoxide may cause low body oxygen, heart disease and brain damage, low baby birth weight and increased foetal death and birth defects.</p> <p>Chronic excessive intake of iron have been associated with damage to the liver and pancreas. People with a genetic disposition to poor control over iron are at an increased risk.</p>	
Tomago Aluminium Remelt Ingot	TOXICITY Not Available	IRRITATION Not Available
aluminium	TOXICITY Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available
silicon	TOXICITY Oral (rat) LD50: 3160 mg/kg ^[2]	IRRITATION Not Available
iron	TOXICITY Oral (rat) LD50: 98600 mg/kg ^[2]	IRRITATION Not Available
zinc	TOXICITY Dermal (rabbit) LD50: 1130 mg/kg ^[2] Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available
copper	TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation (rat) LC50: 0.733 mg/14 h ^[1] Oral (rat) LD50: 300-500 mg/kg ^[1]	IRRITATION Not Available
chromium	TOXICITY Not Available	IRRITATION Not Available
boron	TOXICITY Oral (rat) LD50: 650 mg/kg ^[2]	IRRITATION Not Available
titanium	TOXICITY Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available
strontium	TOXICITY Not Available	IRRITATION Not Available
nickel	TOXICITY Oral (rat) LD50: 5000 mg/kg ^[2]	IRRITATION Not Available
manganese	TOXICITY Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Eye (rabbit): 500 mg/24h - mild Skin (rabbit): 500 mg/24h - mild
magnesium	TOXICITY Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available
welding fumes	TOXICITY Not Available	IRRITATION Not Available

Tomago Aluminium Remelt Ingot

fresh alumina	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available
silica, fumed	TOXICITY	IRRITATION
	Not Available	Not Available
iron oxide fume	TOXICITY	IRRITATION
	Oral (rat) LD50: >5000 mg/kg ^[1]	Not Available
magnesium oxide fume	TOXICITY	IRRITATION
	Not Available	Not Available
copper fume	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: 0.733 mg/l4 h ^[1]	
manganese fume	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) 500mg/24H Mild
		Skin (rabbit) 500mg/24H Mild
chromium fume	TOXICITY	IRRITATION
	Not Available	Not Available
nickel fume	TOXICITY	IRRITATION
	Oral (rat) LD50: 5000 mg/kg ^[2]	Not Available
zinc oxide fume	TOXICITY	IRRITATION
	Oral (rat) LD50: >5000 mg/kg ^[1]	Eye (rabbit): 500 mg/24h mild
		Skin (rabbit): 500 mg/24h mild
nitrogen oxides	TOXICITY	IRRITATION
	Not Available	Not Available
ozone	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 0.001 mg/l/44H ^[2]	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

SILICON	Injection of silicon into the peritoneal cavity produced only minor local trauma and foreign body reaction. In animal testing, silicon dioxide given by mouth did not cause clinical signs or cell changes. Silicon dioxide was largely eliminated in the faeces.
COPPER	for copper and its compounds (typically copper chloride): Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. WARNING: Inhalation of high concentrations of copper fume may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever.
CHROMIUM	Tenth Annual Report on Carcinogens: Substance known to be Carcinogenic [National Toxicology Program: U.S. Dep. of Health and Human Services 2002] Gastrointestinal tumours, lymphoma, musculoskeletal tumours and tumours at site of application recorded.
BORON	Elemental boron produces lower foetal body weight in rats. As dose levels increase the effects seen include rib effects, increased foetal cardiovascular malformations in the rabbit and severe testicular pathology in the rat, including testicular atrophy and sterility. Reduced foetal weight also occurs in mice.
NICKEL	Oral (rat) TDL ₀ : 500 mg/kg/5D-I Inhalation (rat) TCL ₀ : 0.1 mg/m ³ /24H/17W-C
WELDING FUMES	Most welding is performed using electric arc processes. There has been considerable evidence linking welding activities and cancer risk. Several case-control studies reported excess risk of melanoma of the eye in welders. This association may be due to the presence in some welding environments of fumes of thorium-232, which is used in tungsten welding rods. WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS. Not available. Refer to individual constituents.
SILICA, FUMED	For silica amorphous: When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the vast majority of SAS is excreted in the faeces and there is little accumulation in the body. Following absorption across the gut, SAS is eliminated via urine without modification in animals and humans. SAS is not expected to be broken down (metabolised) in mammals.
MAGNESIUM OXIDE FUME	Substance has been investigated as a tumorigen; found to be an equivocal tumorigenic agent by RTECS criteria in rodents.

Tomago Aluminium Remelt Ingot

nitrogen oxides	Data for nitrogen dioxide: Substance has been investigated as a mutagen and reproductive effector. NOTE: Interstitial edema, epithelial proliferation and, in high concentrations, fibrosis and emphysema develop after repeated exposure.
OZONE	NOTE: Ozone aggravates chronic obstructive pulmonary diseases. Ozone is suspected also of increasing the risk of acute and chronic respiratory disease, mutagenesis and foetotoxicity. In animals short-term exposure to ambient concentrations of less than 1 ppm results in reduced capacity to kill intrapulmonary organisms and allows purulent bacteria to proliferate [Ellenhorn etal].
ALUMINIUM & SILICON & CHROMIUM & TITANIUM & STRONTIUM & FRESH ALUMINA & SILICA, FUMED & CHROMIUM FUME	No significant acute toxicological data identified in literature search.
SILICON & BORON & MAGNESIUM OXIDE FUME & nitrogen oxides & OZONE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.
SILICON & MANGANESE & ZINC OXIDE FUME	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
ZINC & MANGANESE & ZINC OXIDE FUME	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
CHROMIUM & CHROMIUM FUME	On skin and inhalation exposure, chromium and its compounds (except hexavalent) can be a potent sensitiser, as particulates. Studies show that they have a complex toxicity mechanism with hexavalent chromium associated with an increased risk of lung damage and respiratory cancers (primarily bronchogenic and nose cancers). However, there is no evidence that elemental, divalent, or trivalent chromium compounds causes cancer or genetic toxicity. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
NICKEL & MAGNESIUM OXIDE FUME & NICKEL FUME	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
NICKEL & NICKEL FUME	WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health & Human Services 2002]

Acute Toxicity	☹	Carcinogenicity	☹
Skin Irritation/Corrosion	☹	Reproductivity	☹
Serious Eye Damage/Irritation	☹	STOT - Single Exposure	☹
Respiratory or Skin sensitisation	☹	STOT - Repeated Exposure	☹
Mutagenicity	☹	Aspiration Hazard	☹

Legend: ✘ – Data available but does not fill the criteria for classification
✔ – Data available to make classification
☹ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Tomago Aluminium Remelt Ingot	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
aluminium	LC50	96	Fish	0.078-0.108mg/L	2
	EC50	48	Crustacea	0.7364mg/L	2
	EC50	96	Algae or other aquatic plants	0.0054mg/L	2
	BCF	360	Algae or other aquatic plants	9mg/L	4
	NOEC	72	Algae or other aquatic plants	>=0.004mg/L	2
silicon	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
EC50	72	Algae or other aquatic plants	ca.250mg/L	2	
iron	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.05mg/L	2
	EC50	96	Algae or other aquatic plants	3.7mg/L	4
	BCF	24	Crustacea	0.000002mg/L	4
NOEC	504	Fish	0.52mg/L	2	
zinc	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.00272mg/L	4
EC50	48	Crustacea	0.04mg/L	5	

Continued...

Tomago Aluminium Remelt Ingot

	EC50	72	Algae or other aquatic plants	0.106mg/L	4
	BCF	360	Algae or other aquatic plants	9mg/L	4
	NOEC	336	Algae or other aquatic plants	0.00075mg/L	4
copper	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0028mg/L	2
	EC50	48	Crustacea	0.001mg/L	5
	EC50	72	Algae or other aquatic plants	0.013335mg/L	4
	BCF	960	Fish	200mg/L	4
	EC25	6	Algae or other aquatic plants	0.00150495mg/L	4
	NOEC	96	Crustacea	0.0008mg/L	4
chromium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	13.9mg/L	4
	EC50	48	Crustacea	0.0225mg/L	5
	EC50	72	Algae or other aquatic plants	0.104mg/L	4
	BCF	1440	Algae or other aquatic plants	0.0495mg/L	4
NOEC	672	Fish	0.00019mg/L	4	
boron	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	74mg/L	2
	EC50	48	Crustacea	230mg/L	5
	EC50	72	Algae or other aquatic plants	54mg/L	2
	BCF	336	Algae or other aquatic plants	8.5mg/L	4
NOEC	576	Fish	0.001mg/L	5	
titanium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
NOEC	48	Crustacea	1mg/L	2	
strontium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
nickel	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0000475mg/L	4
	EC50	48	Crustacea	0.013mg/L	5
	EC50	72	Algae or other aquatic plants	0.0407mg/L	2
	BCF	1440	Algae or other aquatic plants	0.47mg/L	4
NOEC	72	Algae or other aquatic plants	0.0035mg/L	2	
manganese	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>3.6mg/L	2
	EC50	48	Crustacea	>1.6mg/L	2
	EC50	72	Algae or other aquatic plants	2.8mg/L	2
	BCFD	37	Algae or other aquatic plants	2.2mg/L	4
NOEC	48	Crustacea	1.6mg/L	2	
magnesium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	541mg/L	2
	EC50	72	Algae or other aquatic plants	>20mg/L	2
NOEC	72	Algae or other aquatic plants	>25.5mg/L	2	
welding fumes	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
fresh alumina	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0029mg/L	2
	EC50	48	Crustacea	0.7364mg/L	2
	EC50	96	Algae or other aquatic plants	0.0054mg/L	2
NOEC	72	Algae or other aquatic plants	>=0.004mg/L	2	

Tomago Aluminium Remelt Ingot

silica, fumed	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
iron oxide fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.05mg/L	2
	EC50	72	Algae or other aquatic plants	18mg/L	2
	NOEC	504	Fish	0.52mg/L	2
magnesium oxide fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
copper fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0028mg/L	2
	EC50	48	Crustacea	0.001mg/L	5
	EC50	72	Algae or other aquatic plants	0.013335mg/L	4
	BCF	960	Fish	200mg/L	4
	EC25	6	Algae or other aquatic plants	0.00150495mg/L	4
	NOEC	96	Crustacea	0.0008mg/L	4
manganese fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>3.6mg/L	2
	EC50	48	Crustacea	>1.6mg/L	2
	EC50	72	Algae or other aquatic plants	2.8mg/L	2
	BCFD	37	Algae or other aquatic plants	2.2mg/L	4
chromium fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	13.9mg/L	4
	EC50	48	Crustacea	0.0225mg/L	5
	EC50	72	Algae or other aquatic plants	0.104mg/L	4
	BCF	1440	Algae or other aquatic plants	0.0495mg/L	4
nickel fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0000475mg/L	4
	EC50	48	Crustacea	0.013mg/L	5
	EC50	72	Algae or other aquatic plants	0.0407mg/L	2
	BCF	1440	Algae or other aquatic plants	0.47mg/L	4
zinc oxide fume	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.439mg/L	2
	EC50	48	Crustacea	0.105mg/L	2
	EC50	72	Algae or other aquatic plants	0.042mg/L	4
	BCF	336	Fish	4376.673mg/L	4
nitrogen oxides	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
ozone	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0093mg/L	4
	NOEC	2160	Fish	0.002mg/L	5

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Continued...

Tomago Aluminium Remelt Ingot

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
zinc oxide fume	LOW (BCF = 217)

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill. ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	
	NO
HAZCHEM	
	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	

SILICON(7440-21-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
------------------------------	---

IRON(7439-89-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)	
---	--

ZINC(7440-66-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australia Inventory of Chemical Substances (AICS)
--	---

COPPER(7440-50-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4
Australia Inventory of Chemical Substances (AICS)	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix A	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

CHROMIUM(7440-47-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Australia Inventory of Chemical Substances (AICS)	

BORON(7440-42-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4
---	---

TITANIUM(7440-32-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)	International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft
---	---

STRONTIUM(7440-24-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

NICKEL(7440-02-0) IS FOUND ON THE FOLLOWING REGULATORY LISTSAustralia Exposure Standards
Australia Hazardous Chemical Information System (HCIS) - Hazardous ChemicalsAustralia Inventory of Chemical Substances (AICS)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs**MANGANESE(7439-96-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**Australia Exposure Standards
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

MAGNESIUM(7439-95-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

WELDING FUMES(NOT AVAILABLE) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

FRESH ALUMINA(1344-28-1.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

SILICA, FUMED(99439-28-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

IRON OXIDE FUME(1309-37-1.) IS FOUND ON THE FOLLOWING REGULATORY LISTSAustralia Exposure Standards
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs**MAGNESIUM OXIDE FUME(1309-48-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

COPPER FUME(7440-50-8.) IS FOUND ON THE FOLLOWING REGULATORY LISTSAustralia Exposure Standards
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix AAustralia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6**MANGANESE FUME(7439-96-5.) IS FOUND ON THE FOLLOWING REGULATORY LISTS**Australia Exposure Standards
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

CHROMIUM FUME(7440-47-3) IS FOUND ON THE FOLLOWING REGULATORY LISTSAustralia Exposure Standards
Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

NICKEL FUME(7440-02-0) IS FOUND ON THE FOLLOWING REGULATORY LISTSAustralia Exposure Standards
Australia Hazardous Chemical Information System (HCIS) - Hazardous ChemicalsAustralia Inventory of Chemical Substances (AICS)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs**ZINC OXIDE FUME(1314-13-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS**Australia Exposure Standards
Australia Hazardous Chemical Information System (HCIS) - Hazardous ChemicalsAustralia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4**NITROGEN OXIDES(MIXTURE) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

OZONE(10028-15-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

National Inventory Status

National Inventory	Status
Australia - AICS	N (ozone; welding fumes; silica, fumed; nitrogen oxides)
Canada - DSL	N (ozone; welding fumes; silica, fumed; nitrogen oxides)
Canada - NDSL	N (manganese fume; nickel fume; strontium; zinc; copper fume; chromium fume; titanium; magnesium; manganese; silicon; copper; zinc oxide fume; boron; welding fumes; magnesium oxide fume; silica, fumed; iron oxide fume; nitrogen oxides; aluminium; fresh alumina; nickel; iron; chromium)
China - IECSC	N (welding fumes; silica, fumed; nitrogen oxides)
Europe - EINEC / ELINCS / NLP	N (welding fumes; silica, fumed; nitrogen oxides)
Japan - ENCS	N (manganese fume; nickel fume; strontium; zinc; copper fume; chromium fume; ozone; titanium; magnesium; manganese; silicon; copper; boron; welding fumes; silica, fumed; nitrogen oxides; aluminium; nickel; iron; chromium)

Tomago Aluminium Remelt Ingot

Korea - KECI	N (welding fumes; silica, fumed; nitrogen oxides)
New Zealand - NZIoC	N (welding fumes; silica, fumed; nitrogen oxides)
Philippines - PICCS	N (ozone; welding fumes; silica, fumed; nitrogen oxides)
USA - TSCA	N (welding fumes; silica, fumed; nitrogen oxides)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	19/07/2018
Initial Date	14/11/2006

Other information

Ingredients with multiple cas numbers

Name	CAS No
aluminium	7429-90-5, 91728-14-2
silicon	7440-21-3, 152284-21-4, 157383-37-4, 160371-18-6, 17375-03-0, 71536-23-7, 72516-01-9, 72516-02-0, 72516-03-1, 90337-93-2
copper	7440-50-8, 133353-46-5, 133353-47-6, 195161-80-9, 65555-90-0, 72514-83-1
fresh alumina	1344-28-1., 1011245-20-7, 1022097-81-9, 107462-07-7, 107874-14-6, 1097999-44-4, 1197416-35-5, 122784-35-4, 1234495-70-5, 1239586-42-5, 12522-88-2, 127361-04-0, 12737-16-5, 131689-14-0, 1346644-15-2, 135152-65-7, 1355357-83-3, 135667-70-8, 138361-58-7, 148619-39-0, 152743-26-5, 153858-98-1, 157516-29-5, 163581-50-8, 165390-91-0, 170448-81-4, 190401-78-6, 200295-99-4, 205316-36-5, 209552-43-2, 230616-05-4, 252756-35-7, 253606-46-1, 253606-47-2, 253606-45-0, 268724-08-9, 39354-49-9, 457654-46-5, 488831-46-5, 521982-71-8, 53809-96-4, 54352-04-4, 546141-61-1, 663170-52-3, 67853-35-4, 67894-14-8, 67894-42-2, 68189-68-4, 68389-42-4, 68389-43-5, 74871-10-6, 76363-81-0, 84149-21-3, 90669-62-8, 916225-60-0, 960377-08-6, 11092-32-3

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
 TEL (+61 3) 9572 4700.